

Michelin® Retread Technologies Quick Reference Tread Guide

September 2006



 RETREAD TECHNOLOGIES



MICHELIN® RETREADS QUICK REFERENCE TREAD GUIDE

Product Availability (Tread Depth in Shaded Boxes)

Standard Sizes

Tread Size	140	150	160	170	180	190	200	210	220	230	240	250	260	270
Size \ DIE			162 \ 4	168 \ 5	177 \ 6	194 \ 7	203 \ 8	211 \ 8.5N	219 \ 9	225 \ 9.5	232 \ 10	238 \ 10.5	252 \ 12	
Spread Axle Sizes						185	195	205	215	225				
XDA2® 23 AT*								23	23	23	23			
XDA2® 19 AT*							19	19	19	19				
XDA®+ AT*							23	23	23	23				
XDA® Hypersipe										26				
XDA-HT™							28	28	28	28	28			
XD4®							28	28	28	28				
XDN®					17			26	26	26		25		
XDHT® (1)					19	23	23	23	23	23				
XDA®													25	
XDC® LL								14	14					
XDC® 22						22	22	22	22	22				
XDC® 18						18	18	18	18	18				
XM+S4®			21	21	21	21	21	21	21	21				
XDE® M/S			18	18	18	20	20	22	22	22	26	26		
XDS®									25	25		25		
XDU®S											32	32		32
XDY®							26	26	26	26	26	32	32	
XDY-1™								30	30	30	30	30	30	
XZA® (1)	13	13	13	13	13	15	15	15	15	15		20		
XZE® (1)				16	18	18	18	18	18	18				
XZE® SA						18	18	18	18	18				
XZU®S									26	26	26	26		26
XZY®							18	18	18	18	18	20		
XZY-1™								20	20	20	20	20	26	
XZY-2™								26	26	26	26	26		
XT-1® AT* (1)							12	12	12	12				
XTA®-1 (1)						11	11	11	11	11				
XTA®											16		16	
XTY® SA							22	22	22					

For up-to-date product information please visit www.michelintruck.com

**AT* designated Advanced Technology compounds for fuel savings.

(1) Available siped. Consult Michelin Retread Technologies dealers for availability.

Wide Base and X One® Sizes

Tread Size	290	320	350	375	380	390
XTE2® Wide Base	20					
XZA® Wide Base	19	19	19			
XZH™ Wide Base			20			
XZY® Wide Base	20	20	20			
X One® XDA®					24	24
X One® XDA-HT™					26	
X One® XTA®				13		
X One® XTE™				16		

BUFFING SPECS

SCULP	SIZE	LR	BUFF RADIUS mm	BUFF WIDTH mm	OPT BUFF WIDTH
X One XDA	445/50R22.5	L	2000	380	
X One XDA-HT	445/50R22.5	L	2000	380	
X One XTA	445/50R22.5	L	2000	380	
X One XTE	445/50R22.5	L	2000	380	
	455/55R22.5 *	L	2000	390	
XCA	7.5R17	D	300	140	
XD2	285/70R19.5	H	750	225	219
	255/70R22.5	H	850	211	203
XD4	11R22.5	G	675	230	225
	275/80R22.5	G	675	230	225
	275/80R24.5	G	675	230	225
XDA ENERGY	275/80R22.5	G	675	230	225
XDA3	11R22.5	G	675	230	225
	11R24.5	G	675	230	225
XDA-HT	11R22.5	G	675	230	225
	275/80R22.5	G	675	230	225
	275/80R24.5	G	675	230	225
XDE A/T	11R22.5	H	675	230	225
	12R22.5	H	675	230	225
	11R24.5	H	600	224	219
XDE M/S	225/70R19.5	F	500	194	177
	225/70R19.5	G	500	194	177
	245/70R19.5	H	1000	212	203
	10R22.5	F	675	203	194
	10R22.5	G	675	203	194
	11R22.5	G	675	230	225
	235/80R22.5	G	550	194	177
	255/80R22.5	G	600	203	194
	275/80R22.5	G	675	230	225
	9R22.5	F	550	168	152
	11R22.5 *	H	675	230	225
XDE1	215/75R17.5	F	525	177	168
XDE2+	265/70R19.5	G	550	194	177
	285/70R19.5	H	750	225	219
XDHT	11R22.5	G	675	230	225
	275/80R22.5	G	675	230	225
	11R24.5	G	675	230	225
	275/80R24.5	G	675	230	225
XDL	12.00R24	J	675	225	219
XDN GRIP	315/80R22.5	L	700		
XDN2	11R22.5	G	675	240	225
	11R22.5	H	675	240	225
	12R22.5	H	675	252	250
	275/80R22.5	G	675	240	225
XDS	11R22.5	H	675	230	225
	12R22.5	H	675	230	225
XDY 3	11R22.5	H	675	230	225
	11R22.5	G	675	230	225
	315/80R22.5	L	700		
XDY-2	11R22.5	H	675	230	225
XRV	225/70R19.5	F	500	194	177
	245/70R19.5	F	450	193	177
	235/80R22.5	G	550	194	177
	255/80R22.5	G	600	203	194
XT-1	11R22.5	G	675	230	225
	275/80R22.5	G	675	230	225
	11R24.5	G	675	230	225
	275/80R24.5	G	675	230	225
XTA	10.00R15	J	450	177	168
	7.50R15	H	450	152	140
	8.25R15	H	450	152	140
	215/75R17.5	J	525	177	168
XTA ENERGY	275/80R22.5	G	675	230	225
XTA2 ENERGY	245/70R17.5	J	650	203	194
XTE	11R22.5	G	675	230	225
	275/80R22.5	G	675	230	225
	11R24.5	G	675	230	225
	275/80R24.5	G	675	230	225

SCULP	SIZE	LR	BUFF RADIUS mm	BUFF WIDTH mm	OPT BUFF WIDTH	
XTE2	285/70R19.5	J	750	225	219	
XTE2 (Wide Base)	385/65R22.5	L	1300	286		
	425/65R22.5	L	1300	318	290	
	445/65R22.5	L	1200	340	320	
XTY2	275/70R22.5	J	850	225	219	
XZ2	12R22.5	H	675	230	225	
XZA	10R17.5	G	500	168	152	
	8R19.5	F	300	152	140	
	305/70R19.5	J	950	238	232	
XZA3	11R22.5	G	675	230	225	
	11R22.5	H	675	230	225	
	275/80R22.5	G	675	230	225	
	275/80R22.5	H	675	230	225	
	11R24.5	G	675	230	225	
	275/80R24.5	G	675	230	225	
XZA1	315/80R22.5	L	700	240	238	
XZA-1 XZA-1B	11R22.5	G	675	230	225	
	275/80R22.5	G	675	230	225	
	11R24.5	G	675	230	225	
	275/80R24.5	G	600	218	211	
XZA2	11R22.5	G	675	230	225	
	275/80R22.5	G	675	230	225	
	11R24.5	G	675	230	225	
	275/80R24.5	G	675	230	225	
XZA2 Energy	275/70R22.5	J	850	225	219	
	295/80R22.5	H	675	225	219	
	315/80R22.5	L	700			
XZA4	G20 (14.00R20)	M	675	273		
XZE	225/70R19.5	G	500	194	177	
	225/70R19.5	F	500	194	177	
	245/70R19.5	F	600	210	203	
	245/70R19.5	H	1000	211	203	
	9R22.5	F	550	168	152	
	10R22.5	G	675	203	194	
	10R22.5	F	675	203	194	
	11R22.5	G	675	230	225	
	11R22.5 *	H	675	230	225	
	12R22.5 *	H	675	230	225	
	235/80R22.5	G	550	194	177	
XZE1	255/80R22.5	G	600	203	194	
	255/70R22.5 *	H	850	211	194	
	275/80R22.5	G	675	230	225	
	11R24.5	G	675	230	225	
	11R24.5 *	H	675	230	225	
	275/80R24.5	G	675	230	225	
	215/75R17.5	F	525	177	168	
	XZE2	9.00R20	G	600	177	168
		10.00R20	H	600	219	216
		11.00R20	H	600	219	216
		12.00R20	J	675	230	225
XZE2+	265/70R19.5	G	550	194	177	
	285/70R19.5	H	750	225	219	
	275/70R22.5	J	850	225	219	
	295/80R22.5	H	675	225	219	
	425/65R22.5	L	1300	318	290	
XZL (Wide Base)	445/65R22.5	L	1200	365	320	
	12.00R24	J	675	225	219	
XZY	12R22.5	H	675	230	225	
XZY 3 (Wide Base)	385/65R22.5	J	1300	286		
	425/65R22.5	L	1300	318	290	
	445/65R22.5	L	1200	340	320	
XZY-2	11R22.5	H	675	230	225	
	11R24.5	H	675	230	225	

* With tread compound for chip and cut resistance.

RETREAD TREAD DESIGN

DRIVE POSITION

XDA2® 19 Pre-Mold™ Retread XDA2® 23 Pre-Mold™ Retread

- Fuel-efficient Advanced Technology compound
- No compromise performance
- Modified tread block design optimized for long, even wear
- XDA2® 19 - 19/32nds tread depth and XDA2® 23 - 23/32nds tread depth
- XDA2® 23 - also available as a Custom Mold™ retread

				XDA2® 19 Pre-Mold™ Retread Data XDA2® 23 Pre-Mold™ Retread Data		
				Width	XDA2 19 Tread Depth	XDA2 23 Tread Depth
LH	R	O/O	U	203 \ 8.0	19/32"	—
				211 \ 8.5	19/32"	23/32"
				219 \ 9.0	19/32"	23/32"
				225 \ 9.5	19/32"	23/32"
				232 \ 10.0	—	23/32"

XDA® Hypersipe Pre-Mold™ Retread

- Unique, regenerative siping to help maintain traction for more usable 32nds
- Uniform block rigidity helps provide longer, smoother wear
- Compounding and profile yields a cooler running tread and improved rolling resistance for better fuel economy
- Extra high density of cross siping for added traction

				XDA® Hypersipe Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	230	26/32"

XDA®+ AT Pre-Mold™ Retread

- Fuel-efficient Advanced Technology compound
- No compromise performance
- Block design for long mileage and even wear
- 23/32nds tread depth

				XDA®+ Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	203 \ 8.0	23/32"
				211 \ 8.5	23/32"
				219 \ 9.0	23/32"
				225 \ 9.5	23/32"

XDA-HT™ *High Torque* Pre-Mold™ Retread

- Unique two compound design to help deliver long mileage and to help minimize internal casing temperatures
- Solid shoulder design optimized for long, smooth wear
- Open lug design helps provide excellent traction in adverse conditions
- 28/32nds tread depth

				XDA-HT™ Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	200 mm	28/32"
				210 mm	28/32"
				220 mm	28/32"
				230 mm	28/32"
				240 mm	28/32"

XD4® Pre-Mold™ Retread

- Extra deep tread design optimized for high torque applications e.g. 4x2's
- Open shoulder design helps deliver exceptional traction
- 28/32nds tread depth
- Unique scrub resistant compound
- Also available as a Custom Mold™ retread.

				XD4® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	203 \ 8.0	28/32"
				210	28/32"
				220	28/32"
				230	28/32"

XDN® Pre-Mold™ Retread

- Excellent traction levels in snow and ice conditions
- Sipes and lateral inter-locking grooves for rain and snow evacuation
- Excellent mileage
- Square shoulder for stability
- 17/32nds or 26/32nds tread depth - depending on tread width
- Also available as a Custom Mold™ retread

				XDN® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	180 mm	17/32"
				210 mm	26/32"
				220 mm	26/32"
				230 mm	26/32"
				250 mm	25/32"

RETREAD TREAD DESIGN

DRIVE POSITION

XDHT® Pre-Mold™ Retread

- Solid shoulder design optimized for high scrub applications
- Block design optimized for high torque applications
- 19/32nds or 23/32nds tread depth - depending on tread width
- Available siped
- Also available as a Custom Mold™ retread

				XDHT® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	180 mm	19/32"
				194 \ 7.0	23/32"
				203 \ 8.0	23/32"
				211 \ 8.5	23/32"
				219 \ 9.0	23/32"
				225 \ 9.5	23/32"
				232 \ 10.0	23/32"

Recamic® XDA® Pre-Mold™ Retread

- Square shoulder for stability
- Slow, even wear
- Excellent mileage
- 25/32nds tread depth

				Recamic® XDA® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	240 mm	25/32"

XDC® 18 Pre-Mold™ Retread

XDC® 22 Pre-Mold™ Retread

- Open shoulder design optimized for exceptional traction
- Solid center rib promotes long, even wear
- Classic drive axle design helps deliver excellent wear and traction
- XDC® 18 – 18/32nds tread depth and
- XDC® 22 – 22/32nds tread depth

				XDC® 18 Pre-Mold™ Retread Data XDC® 22 Pre-Mold™ Retread Data		
				Width	XDC 18 Tread Depth	XDC 22 Tread Depth
LH	R	O/O	U	194 \ 7.0	18/32"	22/32"
				203 \ 8.0	18/32"	22/32"
				211 \ 8.5	18/32"	22/32"
				219 \ 9.0	18/32"	22/32"
				225 \ 9.5	18/32"	22/32"

XDC® LL Pre-Mold™ Retread

- Designed for trade-in vehicles
- Meets truck manufacturers trade-in requirements

				XDC® LL Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	210	14/32"
				220	14/32"

XM+S4® Pre-Mold™ Retread

- Standard highway compound
- Open lug tread design promotes self-cleaning of lugs and helps maximize mud and snow traction
- Chevron block design for high traction and low noise
- 21/32nds tread depth

				XM+S4® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	162 \ 4.0	21/32"
				168 \ 5.0	21/32"
				177 \ 6.0	21/32"
				194 \ 7.0	21/32"
				203 \ 8.0	21/32"
				211 \ 8.5	21/32"
				219 \ 9.0	21/32"
				225 \ 9.5	21/32"

XDE® M/S Pre-Mold™ Retread

- Open shoulder tread design optimized to help deliver high traction while providing excellent treadwear
- Offset shoulder blocks help provide added traction in mud and soft soil conditions
- 18/32nds, 20/32nds, 22/32nds, or 26/32nds tread depth depending on tread width


				XDE® M/S Pre-Mold™ Retread Data			
				Width	Tread Depth	Width	Tread Depth
LH	R	O/O	U	160 mm	18/32"	210 mm	22/32"
				170 mm	18/32"	220 mm	22/32"
				180 mm	18/32"	230 mm	22/32"
				190 mm	20/32"	240 mm	26/32"
				200 mm	20/32"	250 mm	26/32"

RETREAD TREAD DESIGN

DRIVE POSITION


XDS® Pre-Mold™ Retread

- Unique Michelin compounding and tread siping to help deliver outstanding traction in severe snow conditions
- Extensive full-width sipes and lateral grooves for effective rain and snow evacuation
- Directional tread optimized for traction
- Also available as a Custom Mold™ retread
- 25/32nds tread depth

				XDS® Pre-Mold™ Retread Data	
				Width	Tread Depth
	LH	R	O/O	220 mm	25/32"
				230 mm	25/32"
				250 mm	25/32"


XDU®S Pre-Mold™ Retread

- More rubber mass to aid in scrub resistance
- Exclusive, unique two-layer compound designed to minimize internal casing temperatures for long tread and casing life
- Proprietary compound specifically formulated for demanding, high scrub operations
- Lug design optimized for high scrub, high traction operations
- 32/32nds tread depth

				XDU®S Pre-Mold™ Retread Data	
				Width	Tread Depth
	LH	R	O/O	240 mm	32/32"
				250 mm	32/32"
				270 mm	32/32"


XDY® Pre-Mold™ Retread

- Compound for chip and cut resistance
- Deep tread for traction and mileage
- 26/32nds or 32/32nds tread depth depending on tread width

				XDY® Pre-Mold™ Retread Data	
				Width	Tread Depth
	LH	R	O/O	203 \ 8.0	26/32"
				211 \ 8.5	26/32"
				219 \ 9.0	26/32"
				225 \ 9.5	26/32"
				232 \ 10.0	26/32"
				238 \ 10.5	26/32"
				240 mm	32/32"
				252 \ 12.0	32/32"

XDY-1™ Pre-Mold™ Retread

- Compound for chip and cut resistance
- Directional tread optimized for traction
- Extra deep tread for extra protection and mileage
- 30/32nds tread depth


				XDY-1™ Pre-Mold™ Retread Data	
				Width	Tread Depth
	LH	R	O/O	211 \ 8.5	30/32"
				219 \ 9.0	30/32"
				225 \ 9.5	30/32"
				232 \ 10.0	30/32"
				238 \ 10.5	30/32"
				250 mm	30/32"

RETREAD TREAD DESIGN

ALL-WHEEL POSITION

XZA® Pre-Mold™ Retread


- Solid shoulder to help withstand scrub and abrasion
- Designed for long mileage and even wear
- Available siped
- Also available as a Custom Mold™ retread
- 13/32nds or 15/32nds tread depth depending on tread width

				XZA® Pre-Mold™ Retread Data		
				Width	Tread Depth	
	LH	R	O/O	U	140 mm	13/32"
					150 mm	13/32"
					160 mm	13/32"
					170 mm	13/32"
					180 mm	13/32"
					194 \ 7.0	15/32"
					203 \ 8.0	15/32"
					211 \ 8.5	15/32"
					219 \ 9.0	15/32"
					225 \ 9.5	15/32"
				* 240 mm	20/32"	

* Tread design below available in the 240 mm - 20/32" width only.


XZE® SA Pre-Mold™ Retread

- Rounded shoulders to help minimize scrub effects typical of spread axle applications
- Tapered tread extensions to help withstand shifting footprint stress typical of spread axle applications while helping to maintain casing durability
- 18/32nds tread depth

				XZE® SA Pre-Mold™ Retread Data		
				Width	Tread Depth	
	LH	R	O/O	U	185 mm	18/32"
					195 mm	18/32"
					205 mm	18/32"
					215 mm	18/32"
					225 mm	18/32"


XZE® Pre-Mold™ Retread

- Solid shoulders to help withstand scrub and abrasion
- Deep siping for optimized traction
- Deep tread depth designed for long mileage
- Available siped
- Also available as a Custom Mold™ retread
- 16/32nds or 18/32nds tread depth depending on tread width

				XZE® Pre-Mold™ Retread Data		
				Width	Tread Depth	
	LH	R	O/O	U	168 \ 5.0	16/32"
					177 \ 6.0	18/32"
					194 \ 7.0	18/32"
					203 \ 8.0	18/32"
					211 \ 8.5	18/32"
					219 \ 9.0	18/32"
					225 \ 9.5	18/32"


XZU®S Pre-Mold™ Retread

- More rubber mass to aid in scrub resistance
- Exclusive, unique two-layer compound designed to minimize internal casing temperatures for long tread and casing life
- Proprietary compound specifically formulated for demanding, high scrub operations
- Rib design optimized for high scrub, medium traction operations
- 26/32nds tread depth

				XZU®S Pre-Mold™ Retread Data		
				Width	Tread Depth	
	LH	R	O/O	U	220 mm	26/32"
					230 mm	26/32"
					240 mm	26/32"
					250 mm	26/32"
					270 mm	26/32"

XZY® Pre-Mold™ Retread

- Compound for chip and cut resistance
- Rib design optimized for quiet running and even wear
- All wheel position capable
- Shoulder scallops help provide additional traction
- 18/32nds or 20/32nds tread depth depending on tread width

				XZY® Pre-Mold™ Retread Data		
				Width	Tread Depth	
	LH	R	O/O	U	203 \ 8.0	18/32"
					211 \ 8.5	18/32"
					219 \ 9.0	18/32"
					225 \ 9.5	18/32"
					232 \ 10.0	18/32"
					238 \ 10.5	18/32"
					250 mm	20/32"

RETREAD TREAD DESIGN

ALL-WHEEL POSITION

XZY-1™ Pre-Mold™ Retread

- Compound for chip and cut resistance
- Square shoulder helps increase ground contact
- All-wheel-position capable
- 20/32nds or 26/32nds tread depth depending on tread width

				XZY-1™ Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	211 \ 8.5	20/32"
				219 \ 9.0	20/32"
				225 \ 9.5	20/32"
				232 \ 10.0	20/32"
				238 \ 10.5	20/32"
				252 \ 12.0	26/32"

XZY-2™ Pre-Mold™ Retread

- Compound for chip and cut resistance
- Square buttressed shoulder helps provide impact protection from road hazards
- Zig zag tread grooves and shoulder traction scallops help enhance traction in virtually all weather conditions
- 26/32nds tread depth

				XZY-2™ Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	210 mm	26/32"
				220 mm	26/32"
				230 mm	26/32"
				240 mm	26/32"
				250 mm	26/32"

TRAILER POSITION

XT-1® AT Pre-Mold™ Retread

- Fuel efficient Advanced Technology compound
- No Compromise performance
- 12/32nds tread depth
- Available siped
- Also available as a Custom Mold™ retread

				XT-1® AT Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	203 \ 8.0	12/32"
				211 \ 8.5	12/32"
				219 \ 9.0	12/32"
				225 \ 9.5	12/32"

XTA®-1 Pre-Mold™ Retread

- Solid shoulder to withstand most scrub and abrasion
- No compromise performance
- 11/32nds tread depth
- Available siped
- Also available as a Custom Mold™ retread

				XTA®-1 Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	194 \ 7.0	11/32"
				203 \ 8.0	11/32"
				211 \ 8.5	11/32"
				219 \ 9.0	11/32"
				225 \ 9.5	11/32"

Recamic® XTA® Pre-Mold™ Retread

- Excellent stability
- Good resistance in high scrub operations
- 16/32nds tread depth

				Recamic® XTA® Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	240 mm	16/32"
				260 mm	16/32"

XTY® SA Pre-Mold™ Retread

- Application specific compound for chip and cut resistance
- Tapered tread extensions to help withstand shifting footprint stress typical of spread axle and multi-axle applications
- Aggressive tread design for demanding regional and on/off road trailer operations
- 22/32nds tread depth

				XTY® SA Pre-Mold™ Retread Data	
				Width	Tread Depth
LH	R	O/O	U	195 mm	22/32"
				205 mm	22/32"
				215 mm	22/32"

RETREAD TREAD DESIGN

WIDE BASE RETREADS

XTE2[®] WIDE BASE Pre-Mold[™] Retread

- Wide grooves help provide exceptional water evacuation
- Wide shoulder rib to help resist scrub and abrasion
- Tapered tread extensions to help withstand shifting footprint stress typical of wide base service
- 20/32nds tread depth

				XTE2 [®] WIDE BASE Pre-Mold [™] Retread Data	
				Width	Tread Depth
				290 mm	20/32"
LH	R	O/O	U		

XZH[™] WIDE BASE Pre-Mold[™] Retread

- Compound for abrasion-resistance
- Self-cleaning lugs, open shoulder design for exceptional traction and excellent floatation
- Tapered tread extensions to help withstand shifting footprint stress typical of wide base service
- 20/32nds tread depth

				XZH [™] WIDE BASE Pre-Mold [™] Retread Data	
				Width	Tread Depth
				350 mm	20/32"
LH	R	O/O	U		

XZY[®] WIDE BASE Pre-Mold[™] Retread

- Compound for abrasion-resistance to promote long casing and tread life
- Tapered tread extensions to help withstand shifting footprint stress typical of wide base service
- 20/32nds tread depth

				XZY [®] WIDE BASE Pre-Mold [™] Retread Data	
				Width	Tread Depth
				290 mm	20/32"
				320 mm	20/32"
				350 mm	20/32"
LH	R	O/O	U		

XZA[®] WIDE BASE Pre-Mold[™] Retread

- Wide shoulder rib to help withstand scrub and abrasion
- Tapered tread extensions to help withstand shifting footprint stress typical of wide base service
- 19/32nds tread depth

				XZA [®] WIDE BASE Pre-Mold [™] Retread Data	
				Width	Tread Depth
				290 mm	19/32"
				320 mm	19/32"
				350 mm	19/32"
LH	R	O/O	U		

X ONE RETREADS

X One[®] XDA[®] Pre-Mold[™] Retread

- Unique fuel efficient compound, to help contribute to greater fuel savings
- Deep tread depth offering long tread life and excellent all-weather traction
- 24/32 tread depth

				X One [®] XDA [®] Pre-Mold [™] Retread Data	
				Width	Tread Depth
				380 mm	24/32"
				390 mm	24/32"
LH	R	O/O	U		


RETREAD TREAD DESIGN

X ONE RETREADS

X One® XDA-HT™ Pre-Mold™ Retread


- Aggressive lug-type tread design
- Increased traction*
- Increased tread wear*
- Optimized for Regional and Line Haul operations
- Deep 26/32" tread depth
- Cool Running compound

* Up to 20% versus X One® XDA®

	X One® XDA-HT™ Pre-Mold™ Retread Data		
	Width	Tread Depth	
	380 mm	26/32"	
LH	R	O/O	U


X One® XTA® Pre-Mold™ Retread

- Tread design optimized to promote stability and resistance to uneven wear
- Fuel-efficient Advanced Technology compound
- Tapered tread extensions to help withstand the stress of long haul trailer use
- 13/32 tread depth

	X One® XTA® Pre-Mold™ Retread Data		
	Width	Tread Depth	
	375 mm	13/32"	
LH	R	O/O	U

X One® XTE™ Pre-Mold™ Retread


- Tread design optimized to promote stability and resistance to uneven wear
- Scrub-resistant compound for regional operations
- Tapered tread extensions to help withstand the stress of regional trailer use
- 16/32 tread depth

	X One® XTE™ Pre-Mold™ Retread Data		
	Width	Tread Depth	
	375 mm	16/32"	
LH	R	O/O	U

X ONE RETREADS - CAP AND CASING


X One® XDA® Pre-Mold™ Retread

- Fuel-efficient Advanced Technology compound
- Deep tread depth offering long original tread life and excellent all-weather traction
- 24/32nds tread depth

	X One® XDA® Pre-Mold™ Retread Data		
	Casing Size	Tread Depth	
	445/50R22.5 455/55R22.5	24/32" 24/32"	
LH	R	O/O	U


X One® XTA® Custom Mold™ Retread

- Tread design optimized for stability and resistance to uneven wear
- Available exclusively as a Custom Mold™ retread
- 13/32nds tread depth

	X One® XTA® Custom Mold™ Retread Data		
	Casing Size	Tread Depth	
	445/50R22.5	13/32"	
LH	R	O/O	U

X One® XTE™ Custom Mold™ Retread

- Tread design optimized to promote stability and resistance to uneven wear
- Available exclusively as a Custom Mold™ retread
- 16/32nds tread depth

	X One® XTE™ Custom Mold™ Retread Data		
	Casing Size	Tread Depth	
	445/50R22.5	16/32"	
LH	R	O/O	U



Michelin® Retread Technologies Quick Reference Tread Guide

To learn more please contact
your Michelin Sales Representative or visit
www.michelintruck.com

To order more brochures, please call
Promotional Fulfillment Center
1-800-677-3322, Option #2
Monday through Friday, 9 a.m. to 6 p.m. Eastern Time

MICHELIN NORTH AMERICA, INC., Greenville, South Carolina, USA
MICHELIN NORTH AMERICA (CANADA) INC., Laval, Quebec, Canada
MICHELIN MEXICO S.A. DE C.V., Querétaro, Mexico

AN EQUAL OPPORTUNITY EMPLOYER

© 2006 MNA (09/06)

MYL41642

